

EQUIPMENT SPECIFICATION

The average specification below are given as an indication only.

For any further information please contact:

SHADO srl (SHIPPING AND DELIVERY OVERSEAS)

tel. +39 041 2675300 fax +39 041 2670052 - e-mail: info@shado-srl.com

www.shado-srl.com



20' Standard DRY VAN

Max Payload	Tare	Capacity
28180 Kg	2300 Kg	33,2 Cu.m

INTERNAL

Height	Width	Lenght
2394mm	2350 mm	5897 mm

Door

Height	Width
2278 mm	2341 mm



40' Standard DRY VAN

Max Payload	Tare	Capacity
26630 Kg	3850 Kg	67,7 Cu.m

INTERNAL

Height	Width	Lenght
2394 mm	2350 mm	12030 mm

Door

Height	Width
2278 mm	2341 mm



40' High Cube Dry

Max Payload	Tare	Capacity
26280Kg *29000 Kg	4200 Kg *4000 Kg	76,3 Cu.m

*Yellow Series

INTERNAL

Height	Width	Lenght
2699 mm	2350 mm	12030 mm

Door

Height	Width
2583 mm	2338 mm



20' Open Top

Max Payload	Tare	Capacity
28250 Kg	2230 Kg	32 Cu.m

INTERNAL

Height	Width	Lenght
2351 mm	2350-2230* mm * above 2104 mm	5890 mm

Door

Height	Width
2279 mm	2338-1948* mm * above 2279 mm



20' Open Top High Cube


Max Payload	Tare	Capacity
28070 Kg	2410 Kg	40,0 Cu.m

INTERNAL

Height	Width	Lenght
2651 mm	2350-2230* mm * above 2104 mm	5890-5795* * above 2104 mm

Door

Height	Width
2279 mm with swinging header closed	2338-1948* mm * above 2279 mm



40' Open Top

Max Payload	Tare	Capacity
26780 Kg	3700 Kg	67 Cu.m

INTERNAL

Height	Width	Lenght
2351 mm	2350-2230* mm * above 2104 mm	12024 mm

Door

Height	Width
2279 mm	2338-1948 *mm * above 2279 mm



40' Open Top High Cube

Max Payload	Tare	Capacity
26480 Kg	4000 Kg	75 Cu.m

INTERNAL

Height	Width	Lenght
2656 mm	2350-2230* mm * above 2286 mm	12024 mm

Door

Height	Width
2584 mm	2338-1948* mm * above 2584 mm



40' Pallet Wide - Sea Cell


Max Payload	Tare	Capacity
29900 Kg	4100 Kg	70,1 Cu.m

INTERNAL

Height	Width	Lenght
2389 mm	2426 mm	12100 mm

Door

Height	Width
2280 mm	2360 mm



40' Pallet Wide - Sea Cell High Cube

Max Payload	Tare	Capacity
29850 Kg	4150 Kg	79,1 Cu.m

INTERNAL

Height	Width	Lenght
2694 mm	2426 mm	12100 mm


Door

Height	Width
2585 mm	2360 mm



EQUIPMENT SPECIFICATION

The average specification below are given as an indication only.



45' High Cube Pallet Wide

Max Payload	Tare	Capacity
29270 Kg	4730 Kg	88,0 Cu.m

INTERNAL

Height	Width	Lenght
2670 mm	2430 mm	13510 mm

Door

Height	Width
2570 mm	2430 mm



40' Flat Rack High Cube


Max Payload	Tare
39300 Kg	5700 Kg

INTERNAL

Height	Width	Lenght
2220 mm	2370 mm	12118 mm

Between Corner Post Collapsed

Width	Lenght	Height
2110 mm	11840 mm	648 mm



40' Super High Pallet Wide



Max Payload	Tare	Capacity
26020 Kg	4460 Kg	84 Cu.m

EXTERNAL

Height	Width	Lenght
3080 mm	2438 mm	12192 mm

INTERNAL

Height	Width	Lenght
2885 mm	2417 mm	12100 mm

DOOR

Height	Width
2762 mm	2349 mm



40' Platform

Max Payload	Tare
40700 Kg	4300 Kg

INTERNAL

Height	Width	Lenght
625 mm	2380 mm	12110 mm

Between Upper Corner Casting

Width	Lenght
2098 mm	11765 mm



20' Flat Rack

Max Payload	Tare
31220 Kg	2780 Kg

INTERNAL

Height	Width	Lenght
2233 mm	2174 mm	6042 mm

Between Corner Post Collapsed

Width	Lenght	Height
2226 mm	5638 mm	370 mm



40' Reefer High Cube

Max Payload	Tare	Capacity
29900 Kg	4100 Kg	66,1 Cu.m

INTERNAL

Height	Width	Lenght
2505 mm	2286 mm	11557 mm

Door

Height	Width
2478 mm	2286 mm



40' Flat Rack

Max Payload	Tare
40500 Kg	4950 Kg

INTERNAL

Height	Width	Lenght
1955 mm	2380 mm	12176 mm

Between Corner Post Collapsed

Width	Lenght	Height
2230 mm	11776 mm	648 mm



20' Reefer

Max Payload	Tare	Capacity
27590 Kg	2890 Kg	28,4 Cu.m

INTERNAL

Height	Width	Lenght
2273 mm	2294 mm	5456 mm

Door

Height	Width
2264 mm	2290 mm